






## 572 NICOLETTE SIDE CHAIR

---



### OVERALL DIMENSIONS:

					
41	24.5	20	19.5	n/a	<b>INCHES</b>

### YARDAGE:






COM: (1.5 yards each – based on plain, non-directional, no repeat textile)

## 573 NICOLETTE ARM CHAIR

---



### OVERALL DIMENSIONS:

					
41	24.5	23.4	19.5	27.5	<b>INCHES</b>

### YARDAGE:

COM: (1.5 yards each – based on plain, non-directional, no repeat textile)

### SPECIFICATION:

- Frame shall be constructed from solid kiln dried beech. Lumber to be dried to a final moisture content between 6% - 8%.
- Front Legs to be constructed from single stock lumber. Turned and carved (tapering from top to bottom) as per photo.
- Rear legs to be constructed from single stock lumber cut to shape. Turned and carved (tapering from top to bottom) as per photo.
- Back to be constructed from solid curved wood. Back to exhibit a 26" radius curved by use of radio frequency and saw cut from solids. Top of back slat is to be eased at top.
- Frame and seat frame are connected together by dowels, corner blocks, bolts and glue.
- Seat shall be ½" thick solid core ply with webbing and applied to the solid beech frame. The seat is attached to the beech frame via screws. High density CAL 117 FR foam and upholstery are applied after assembly.