

## 759G REGGI GRAND SIDE CHAIR SERIES

---



759G-UPOS  
(PULLOVER SEAT)



759G-UWRS  
(WRAPPED SEAT)



759G-WS  
(WOOD SEAT)

### OVERALL DIMENSIONS:



35.5    19.5    19.5    18.5    INCHES

### DIMENSIONS ARE APPROXIMATE

### COM YARDAGE:

759G-UPOS (PULLOVER): 0.75 yards for every 02 chairs (based on no repeat, non-directional material)

759G-UWRS (WRAPPED): 1.75 yards for every 02 chairs (based on no repeat, non-directional material)

*\*Chair also available in WB (Wood Back) versions.*

### SPECIFICATIONS:

- Chair frame and all exposed wood to be constructed from solid kiln dried beech wood. Lumber to be dried to a final moisture content level between 6% - 8%.
- Front legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 1 ½" x 1 ¾" tapering to ¾" x ¾" at bottom.
- Rear legs to be constructed from single stock lumber cut to shape. Finished dimensions are 1" x 1 ½" tapering to ¾" x 1" at bottom. The top of the chair back is integrally joined to the back legs.
- The seat shall be ½" thick solid core beech wood ply and applied to the solid beech wood frame. The seat is attached and screwed to the beech wood frame.
- Back is curved by way of radio frequency constructed from solid beech wood ½" x 1" glued by way of mortise and tenon into the solid beech wood frame.
- Stretchers in solid wood are attached by way of mortise and tenon into the front back legs for added strength.



- The chair frame and seat frame are connected together by dowels, corner blocks, bolts and glue. The frame is finished in any standard ISA wood finish, and a clear lacquer coat for added durability.
- Seat foam is 2" thick, high-density meeting CAL-117 FR on UPOS and UWRS models.
- Includes nail-in nylon glides suitable for most flooring types.