




429-WS/WB SCHOLAR



OVERALL DIMENSIONS:

					
32.5	19.5	20	20	n/a	INCHES

YARDAGE:

N/A

429-UPOS/WB SCHOLAR



OVERALL DIMENSIONS:

					
32.5	19.5	20	20	n/a	INCHES





YARDAGE:

COM: (0.75 yard per every 2 chairs – based on plain, non-directional, no repeat textile)

429-USP/WB SCHOLAR



OVERALL DIMENSIONS:

					
32.5	19.5	20	20	n/a	INCHES

YARDAGE:

COM: (0.75 yard per every 2 chairs – based on plain, non-directional, no repeat textile)

429-USP/UBP SCHOLAR



OVERALL DIMENSIONS:

					
32.5	19.5	20	20	n/a	INCHES

YARDAGE:

COM: (0.75 yard per chair – based on plain, non-directional, no repeat textile)

SPECIFICATION:

- Chair frame is constructed from 16 gauge round metal tubing 1 1/2" dia. at the top tapering down to 1" dia. at the bottom.
- The frame is welded together with a 16 ga. X 1.5" metal strap. The back support is 3/4" square and welded to the frame for added strength.
- Bottoms of legs are capped with 1" dia. Ball plastic chair glides.
- Wood back and wood seat version is 5/8" thick hardwood maple plywood that has been pressed to shape.
- Seat and back is connected to the back support.
- The seat is 1/2" thick solid core plywood applied to the solid beech frame. The seat is attached to the beech frame via screws. High density CAL 117 FR foam and upholstery are applied after assembly.
- The metal frame is finished in any of ISA's standard powder coat/plated finishes, custom colors may be available depending on quantity and color.
- Exposed wood (WB or WS) is finished in any of the ISA wood stains, which are a catalyzed urethane finish, two coats minimum