

445 MOSCATO SIDE CHAIR



OVERALL DIMENSIONS:



33 23 22 19 n/a INCHES

YARDAGE:

COM: 1.75 YARDS per chair (based on based on plain, non-directional, no repeat textile)

446 MOSCATO ARM SIDE CHAIR



OVERALL DIMENSIONS:



33 23 22 19 26.5 INCHES

YARDAGE:

COM: 2 YARDS per chair (based on based on plain, non-directional, no repeat textile)

1445 MOSCATO BAR



OVERALL DIMENSIONS:



43 23 23 31 n/a INCHES

YARDAGE:

COM: 1.75 YARDS per chair (based on based on plain, non-directional, no repeat textile)

1446 MOSCATO ARM BAR



OVERALL DIMENSIONS:



43 23 23 31 37 INCHES

YARDAGE:

COM: 2.5 YARDS per chair (based on based on plain, non-directional, no repeat textile)

SPECIFICATION:

- Frame shall be constructed from solid ash. Lumber to be dried to a final moisture content level between 6% - 8%.
- Front legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 2" x $\frac{3}{4}$ " tapering to 1 $\frac{1}{4}$ " x $\frac{3}{4}$ " at bottom.
- Rear legs to be constructed from single stock lumber cut to shape. Finished dimensions are 2" x 1 $\frac{1}{4}$ " and tapers to the bottom.
- The seat rails are made from single stock lumber 2" x 2 $\frac{1}{4}$ " and shaped to conform to the chair design and are glued dowelled and screwed together with corner blocks.
- The seat shall be $\frac{1}{2}$ " thick solid core ply with webbing and applied to the solid oak hardwood frame. The seat is attached and screwed to the hardwood frame.
- The curved back is made of single piece formed plywood screwed into the seat frame.
- $\frac{3}{4}$ " high density CAL 117 FR foam and Dacron wrap is applied to the seat, $\frac{1}{2}$ " thick foam on the inside back and $\frac{1}{4}$ " thick foam on the outside back.