






1422 SANTIAGO BAR



OVERALL DIMENSIONS:

					
43.5	21.5	19.5	31	N/A	INCHES

DIMENSIONS ARE APPROXIMATE

YARDAGE:

COM: 2 yards per stool (based on based on plain, non-directional, no repeat textile)

SPECIFICATION:

- Stool frame shall be constructed from solid kiln dried beech wood. Lumber to be dried to a final moisture content level between 6% - 8%.
- Front legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 1 ½" x 1 ½" tapering to 1 ¼" x 1 ¼" at bottom.
- Rear legs to be constructed from single stock lumber cut to shape. Finished dimensions are 1 ½" x 2" and tapers to 1 ¼" x 1 ½" at bottom.
- The seat rails are made from single stock lumber 2" x 3" and shaped to conform to the chair design and are glued dowelled and screwed together with corner blocks.
- The seat shall be ¾" thick solid core ply and applied to the solid hardwood frame. The seat is attached to the hardwood frame and screwed to the frame.
- The curved back is a single piece formed plywood screwed into the seat frame.
- A stretcher 1" x 1 ¾" is mortised and tenoned into the front legs and the back legs for added strength.
- Foam is 2" high density CAL 117 foam on the seat and ½" on the inside and outside back.
- Also available in counter height.