

284 LASLO



OVERALL DIMENSIONS:



DIMENSIONS ARE APPROXIMATE

YARDAGE:

COM: 2 yards per chair (based on based on plain, non-directional, no repeat textile)

1284 LASLO STOOL



OVERALL DIMENSIONS:



DIMENSIONS ARE APPROXIMATE

YARDAGE:

COM: 1.5 yards per stool (based on based on plain, non-directional, no repeat textile)

SPECIFICATION:

- Frame to be constructed from solid kiln dried beech. Lumber to be dried to a final moisture content between 6% - 8%.
- Front Legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 1³/₄" x 1³/₄" tapering to 1" x 1" at bottom.



- Rear legs to be constructed from single stock lumber cut to shape. Finished dimensions are 1¼” x 1½” and tapering to 1¼” x 1” at bottom.
- All legs are to be connected by way of solid beech seat rails through mortise and tenon.
- Side stretchers run between front and back legs, which are dowelled and glued together.
- The assembled chair is connected together by dowels, corner blocks, bolts and glue, in order to strengthen the chair’s construction.
- The seat shall be ½” thick solid core ply with webbing and applied to the solid beech frame. The seat is attached to the beech frame via screws. High density CAL 117 FR foam and upholstery are applied after assembly.
- Upholstery is a tight pull over for the seat and stapled at the bottom.