

394G MAESTRO CHAIR SERIES



394G-SMLG



394G-TMLG



394G-TWLG



394G-PLGB/PLGW



394G-DKB

OVERALL DIMENSIONS:



33.5 23.5 22 ≈18.5 INCHES

DIMENSIONS ARE APPROXIMATE AND MAY VARY BASED ON LEG STYLE

YARDAGE:

COM: 1.75 yards per chair (based on non-directional, no-repeat material)

Memo sample testing is required for this product, if fabric has not been previously approved

SPECIFICATION:

- Chair starts with a cold molded foam shell, which is made from a metal frame injected with PU foam.
- Shell seat is then wrapped in ¼" high density CAL 117 FR foam.
- Shell back and sides is wrapped in Dacron and upholstered as per specifications
- Available with the following bases:
 - 1) **Straight Metal Leg (SMLG)** - Manufactured using Ø16mm steel tubing. Available in any standard ISA metal finishes.
 - 2) **Tapered Metal Legs (TMLG)** - Manufactured using 16 gauge steel tube. Leg is Ø38 mm at the top tapering down to Ø16 mm. Available in any standard ISA metal finishes.
 - 3) **Tapered Wood Legs (TWLG)** – Made of solid Ash. Leg is Ø38 mm at the top tapering down to Ø25 mm. Available in any standard ISA wood finish.
 - 4) **Beech Plywood Legs (PLGB) / Walnut Plywood Legs (PLGW)**- High frequency molded with 30 layers, 1 1/8" thick. Legs taper from 2" at the top to 1 ¼" at the bottom. Profile is machined for an aesthetic V-shape. Available in any ISA standard wood finishes.
 - 5) **Desk Base (DKB)** - Five prong base constructed from chromed cast aluminum with chrome capped dual wheel casters. *Approximate Dims for DKB: H 32.5"-34" / D 27 / W 27*