

## 400 - 1400 LONSDALE SERIES





### **OVERALL DIMENSIONS:**



## **OVERALL DIMENSIONS:**



# **DIMENSIONS ARE APPROXIMATE**

### YARDAGE:

COM: 2 yards per chair/stool (based on based on plain, non-directional, no repeat textile).

### **SPECIFICATION:**

- Chair frame shall be constructed from solid kiln dried beech wood. Lumber to be dried to a final moisture content between 6% -8%.
- Front Legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 1 3/4" x 1 3/4" tapering to 1" x 1" at bottom.
- Rear legs to be constructed from single stock lumber cut to shape. Finished dimensions are 1 ½" x 1 ½", tapering to 1" x 1 ¾" at bottom.
- The seat shall be 1/2" thick solid core beech wood ply and applied to the solid beech wood frame. The seat is attached to the beech wood frame and laminated with glue via cold press with no less than 200 lbs. of even pressure for application.
- Back to be constructed from a flat beech wood ply, front and back, applied to the solid wood frame.
- Front and rear legs are attached by a solid beech frame that is 2 ½" x 1 ¾".



- Side stretchers fit into the front and back legs via dowels and glue. On Barstools front stretchers include a metal footrest finished in Black, Brass or Satin Aluminum.
- Frames are finished in any standard ISA wood finish and receive a low-gloss clear coat for added durability.
- Frames included nail-in nylon glides suitable for all flooring types.
- The stool is also available in Counter stool (24" seat height).