

594G RAY GRAND



OVERALL DIMENSIONS:



YARDAGE:

COM: 1.75 yards per chair (based on based on plain, non-directional, no repeat textile)

DIMENSIONS ARE APPROXIMATE

1594 RAY STOOL



OVERALL DIMENSIONS:



YARDAGE:

COM: 1.5 yards per chair (based on based on plain, non-directional, no repeat textile)

DIMENSIONS ARE APPROXIMATE

SPECIFICATION:

- Frame to be constructed from solid kiln dried beech wood. Lumber to be dried to a final moisture content between 6% - 8%.
- Front legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 1 5/8" x 1 5/8" tapering to 1 1/4" x 1 1/4" at bottom.
- Rear legs to be constructed from single stock lumber cut to shape. Finished dimensions are 1 1/4" x 1 1/4" and tapers top and bottom. The top of the chair back is integrally joined to the back legs.
- The seat shall be 5/8" thick plywood upholstered and applied to the solid beech wood frame. The seat is upholstered and attached to the beech wood frame and screwed to the frame



- Front, back and side stretchers are standard for are mortised and tenoned into the legs for added strength and durability.
- Back is solid beech wood that is mortised and tenoned into the upper portion of the back legs and then upholstered.
- The frame and seat frame are connected together by dowels, corner blocks, bolts and glue.
- Upholstery is high density FR foam box seat and pull-over back.
- All exposed natural woods are clear coated with polyurethane with a matte finish, all stains are penetrating type with the following application procedure: 1) first coat of penetrating stain; 2) sealer added; 3) sand all show wood; 4) shade stain for consistency; 5) clear coat matte polyurethane added; 6) light sanding; 7) final clear coat.
- Floor contact points are nylon nail in type glides Note: mechanically secured glides have a tenancy to mark flooring when the screw head gets exposed by wear.
- Stool version also available as a counter stool at 24" seat height.