

## 460 ZEN STACK

---



**OVERALL DIMENSIONS:**



30 21 23.5 n/a INCHES

**YARDAGE:**

COM: 0.75 yards per every 2 chairs (based on based on plain, non-directional, no repeat textile)

DIMENSIONS ARE APPROXIMATE

## 461 ZEN ARM STACK

---



**OVERALL DIMENSIONS:**



30 21 24 26.5 INCHES

**YARDAGE:**

COM: 1 yard per every 2 chairs (based on based on plain, non-directional, no repeat textile)

DIMENSIONS ARE APPROXIMATE

## 462 ZEN ARM LOUNGE

---



**OVERALL DIMENSIONS:**



29 23.5 27.5 25 INCHES

**YARDAGE:**

COM: 1.5 yards per chair (based on based on plain, non-directional, no repeat textile)

DIMENSIONS ARE APPROXIMATE

1460 ZEN ARM BARSTOOL



OVERALL DIMENSIONS:



YARDAGE:

COM: 0.75 yards per stool (based on based on plain, non-directional, no repeat textile)

DIMENSIONS ARE APPROXIMATE

SPECIFICATION:

- Frame to be constructed from solid kiln dried oak. Lumber to be dried to a final moisture content between 6% - 8%.
- Front legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 1 ¾" x 1" tapering to 1 ½" x 1" at bottom.
- Rear legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 1 ¾" x 1" tapering to 1 ½" x 1" at bottom.
- Back legs, sculptured back and back support are integral design elements.
- The frame and seat frame are connected together by dowels, corner blocks, bolts and glue.
- The seat shall be ½" thick solid core ply attached to the solid oak frame. The seat is attached to the frame via screws. High density CAL 117 FR foam and upholstery are applied after assembly.
- The stretchers on the barstool run front to back leg and are dowelled and glued together. Front stretcher to have metal footrest - Available in satin aluminum, brass or black.
- Includes nailed in nylon glides suitable for all floorings.