

**490-83 / 491-83 / 1490-83 - ARAMIS SERIES**

---



490-83 SIDE STACK



491-83 STACK ARM



1490-83 BAR STOOL

**OVERALL DIMENSIONS 490-83 SIDE CHAIR:**



33.5 20.5 19 N/A INCHES

DIMENSIONS ARE APPROXIMATE

---

**OVERALL DIMENSIONS 491-83 SIDE CHAIR:**



33.5 20.5 23 26 INCHES

DIMENSIONS ARE APPROXIMATE

---

**OVERALL DIMENSIONS 1490-83 BAR STOOL:**



42 20.5 17.5 N/A INCHES

DIMENSIONS ARE APPROXIMATE

**YARDAGE:**

490-83 SIDE CHAIR: 1.5 yards per chair (based on based on plain, non-directional, no repeat textile)

491-83 ARM CHAIR: 1.5 yards per chair (based on based on plain, non-directional, no repeat textile)

1490-83 BAR STOOL: 1.25 yards per chair (based on based on plain, non-directional, no repeat textile)



## SPECIFICATIONS:

- Chair frame to be constructed from solid kiln dried beech wood. Lumber to be dried to a final moisture content level between 6% - 8%.
- Front legs to be constructed from single stock lumber. Finished dimension at the top of leg to be approximately 1 $\frac{3}{4}$ " x 1 $\frac{3}{4}$ " tapering to 1" x 1" at bottom.
- Rear legs to be constructed from single stock lumber cut to shape. Finished dimensions are approximately 1 $\frac{1}{2}$ " x 1 $\frac{1}{2}$ " tapering to 1"x 1 $\frac{1}{4}$ " at bottom.
- Front and rear legs and attached by a solid beech frame that is 2 $\frac{1}{2}$ " x 1 $\frac{3}{4}$ ".
- Side stretchers run front to back leg and are dowelled and glued together.
- On 1490-83 Barstool double stretchers are added on the sides and single stretchers are added on front and back. Front stretcher covered with metal footrest available in Black, Satin Aluminum or Brass finish.
- The chair frame, arms and seat frame are connected together by dowels, corner blocks, bolts and glue. The frame is stained in any standard ISA wood finish and a clear lacquer is applied for protection (medium sheen).
- The seat is to be  $\frac{1}{2}$ " thick solid core ply, applied to the solid beech frame. The seat is attached to the beech frame via screws. Foam meeting CAL-117 and specified upholstery material are applied after assembly.
- Plywood back is curved  $\frac{1}{2}$ " thick beech that is glued & doweled to the back upright.
- All models include nail in nylon glides suitable for all flooring.