

889 BARRIO SERIES



OVERALL DIMENSIONS:



YARDAGE:

COM: 1(2) yards per chair (based on non-directional, no-repeat material)

SPECIFICATION:

- Back to be constructed from ½" thick formed solid core plywood.
- Seat to be ¾" thick solid core plywood
- Foam is to be CAL 117 2013 high density on the seat and back. Foam will be 1 ½" thick 2.5 lbs. on the seat, 1" thick 1.9 lbs. on the inside back, and ½" thick 1.5 lbs. on the outside back.
- Plywood legs are high frequency molded with 30 layers, 1 1/8" thick. Top legs tapper from 2" to 1 1/4" at the bottom. Profile is machined to an aesthetic V shape.
- Available with the following bases:
 - 1) Straight Metal Legs (SMLG) is manufactured using Ø16 mm steel tubing. Available in any standard ISA powder coat finish and platted finishes.
 - 2) Tapered Metal Legs (TMLG) is manufactured using Ø38 mm, 16 gauge steel tube. Leg is Ø38 mm at the top and tapers down to Ø16 mm. Available in any standard ISA powder coat finish and platted finishes.
- 3) Tapered Wood Legs (TWLG) Ash stained in any standard ISA wood finishes
 - 4) Plywood Legs (PLGB/PLGW) Walnut or Beech wooden legs. Plywood legs available in any standard ISA wood finish.
 - 5) Desk Base (DKB) Five prong base shall be constructed from chromed cast aluminum with chrome capped dual wheel casters. *Dims for DKB: H 31"-34" / D 27 / W 27*
- Push-in glides will be used with available options in metal or polyethylene.