

113G GRAMERCY GRAND SIDE CHAIR



113G-UB (UPH. BACK)



113G-OVB (VENEER BACK)

OVERALL DIMENSIONS:



33 25 23 18 n/a INCHES

DIMENSIONS ARE APPROXIMATE

YARDAGE:

COM (UB): 2.5 yards per chair
COM (OVB): 1.75 yards per chair

(based on based on plain, non-directional, no repeat textile)

114 GRAMERCY SIDE CHAIR



114-UB (UPH. BACK)



114-OVB (VENEER BACK)

OVERALL DIMENSIONS:



30 23 20 18 n/a INCHES

DIMENSIONS ARE APPROXIMATE

YARDAGE:

COM (UB): 2 yards per chair
COM (OVB): 1.75 yards per chair

(based on based on plain, non-directional, no repeat textile)

115G GRAMERCY ARM CHAIR



115G-UB (UPH. BACK)

OVERALL DIMENSIONS:



32 25 23.5 18 25.5 INCHES

DIMENSIONS ARE APPROXIMATE

YARDAGE:

COM (UB): 2.5 yards per chair

(based on based on plain, non-directional, no repeat textile)

1114 GRAMERCY STOOL



1114-UB (UPH. BACK)



1114-OVB (VENEER BACK)

OVERALL DIMENSIONS:



43.5 22.5 19.5 31 n/a INCHES

DIMENSIONS ARE APPROXIMATE

YARDAGE:

COM (UB): 2 yards per chair

COM (OVB): 1.75 yards per chair

(based on based on plain, non-directional, no repeat textile)

SPECIFICATION:

- Chair and Stool frame shall be constructed from solid kiln dried hardwood. Lumber to be dried to a final moisture content between 6%-8%.
- CHAIRS: Front Legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 1 3/4" x 1 7/8" tapering to 1"x1" at bottom. Rear legs to be constructed from single stock lumber cut to shape. Finished dimensions are 1 3/4"x 2 1/4" and tapers to the bottom.
- STOOLS: Front legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 1 1/2" x 1 1/2" tapering to 1 1/4" x 1 1/4" at bottom. Rear legs to be constructed from single stock lumber cut to shape. Finished dimensions are 1 1/2" x 2" and tapers to 1 1/4" x 1 1/2" at bottom.
- The seat rails are made from single stock lumber 2"x3" and shaped to conform to the chair design and are glued dowelled and screwed together with corner blocks.
- The seat shall be 3/4" thick solid core plywood and applied to the solid hardwood frame. The seat is attached and screwed to the hardwood frame.
- The curved back and arms are a single piece formed plywood screwed into the seat frame.
- Veneer backs can be stained in any standard ISA wood finish. A low-gloss clear coat is applied for added finish durability.
- Stretchers (1"x1") are attached via mortise and tenon into the front and rear legs for added strength. On the stools, a 1" x 1 3/4" front stretcher is added, covered in a metal footrest available in Black, Brass or Satin aluminum finish.
- Foam is 2" high density CAL 117 foam on the seat and 1/2" on the inside and outside backs. The back and seat upholstery is a single pull over sleeve.
- The stools are also available in Counter height (24" seat height).