

**1416 FRESNO STOOL SERIES**

---



1416-UPOS  
(PULLOVER SEAT)



1416-UWRS  
(WRAPPED SEAT)



1416-USP  
(SEAT PAD)



1416-WS  
(WOOD SEAT)

**OVERALL DIMENSIONS:**



44    21.5    18    30.5    INCHES

**DIMENSIONS ARE APPROXIMATE**

**COM YARDAGE:**

1416-UPOS (PULLOVER): 0.75 yards for every stool (based on no repeat, non-directional material)

1416-UWRS (WRAPPED): 2.75 yards for every 02 stool (based on no repeat, non-directional material)

1416-USP (SEAT PAD): 0.75 yards for every stool (based on no repeat, non-directional material)

*\*All upholstered stools above are also available in WB (Wood Back) versions. Yardages vary.*

---

**SPECIFICATIONS:**

- Stool frame and all exposed wood to be constructed from solid kiln dried beech wood. Lumber to be dried to a final moisture content level between 6% - 8%.
- Front legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 1 1/2" x 1 3/4" tapering to 3/4" x 3/4" at bottom.
- Rear legs to be constructed from single stock lumber cut to shape. Finished dimensions are 1" x 1 1/2" tapering to 3/4" x 1" at bottom. The top of the chair back is integrally joined to the back legs.
- The seat shall be 1/2" thick solid core beech wood ply and applied to the solid beech wood frame. The seat is attached and screwed to the beech wood frame.
- Back is curved by way of radio frequency constructed from solid beech wood 1/2" x 1" glued by way of mortise and tenon into the solid beech wood frame.



- A “U” type stretcher  $\frac{3}{4}$ ” x  $\frac{3}{4}$ ” is attached by way of mortise and tenon into the front legs and screwed into the back legs for added strength.
- The stool frame and seat frame are connected together by dowels, corner blocks, bolts and glue. The frame is finished in any standard ISA wood finish, and a clear lacquer coat for added durability.
- Seat foam is 2” thick, high-density meeting CAL-117 FR on UPOS and UWRS models. Seat pad (USP) foam is 1” thick.
- Includes nail-in nylon glides suitable for most flooring types.