

1903 CABANA BAR



OVERALL DIMENSIONS:



DIMENSIONS ARE APPROXIMATE AND MAY VARY DEPENDING ON BASE STYLE

YARDAGE:

COM: 2 yards per chair (based on based on plain, non-directional, no repeat textile)

SPECIFICATION:

- Chair back constructed from 1/2" thick formed solid core plywood
- Seat constructed of ¾" solid core plywood
- Foam applied on chair is high density CAL 117. Foam is 1 ½" thick, 2.5 lbs. on the seat; 1" thick, 1.9 lbs. on the inside back and 1 ½" thick, 1.5 lbs. on the outside back.
- Frame to be constructed of ¾" diameter 16 gage steel tube with a polished chrome finish.
- Seat and back of the chair are upholstered separately and mechanically assembled to the frame.
- Seat and back are connected together using steel fabricated connector brackets.
- Push-in glides will be used with available options in metal or polyethylene.
- Straight Metal Leg (SMLG) version is manufactured using Ø16 mm steel tubing. Available in any standard ISA powder coat finish and P77 Polished Chrome
- Tapered Metal Legs (TMLG) version is manufactured using Ø38 mm, 16 gauge steel tube. Leg is Ø38 mm at the top and tapers down to Ø16 mm. Available in any standard ISA powder coat finish and P77 Polished Chrome.
- Tapered Wood Legs (TWLG) are tapered and made from Ash wood. Leg is Ø40 mm at the top tapering down to Ø25 mm.
 Available in any standard ISA wood finish.

46 Dufflaw Road Toronto ON M6A 2W1 | 416-782-9100 | 1-800-881-3928 | www.havaseat.com | isa@havaseat.com