

## 1903-WSWB CABANA STOOL

---



### OVERALL DIMENSIONS:

					
±45.5	±25	±21	±31.5	N/A	INCHES

### DIMENSIONS ARE APPROXIMATE

### YARDAGE:

COM: 2 yards per stool (based on based on plain, non-directional, no repeat textile)

### SPECIFICATION:

- Back of shell constructed from ½” thick formed solid core plywood
- Seat constructed of ¾” solid core plywood
- Foam applied on shell is high density CAL 117. Foam is 1 ½” thick, 2.5 lbs. on the seat; 1” thick, 1.9 lbs. on the inside back and 1 ½” thick, 1.5 lbs. on the outside back.
- Seat and back of the chair are upholstered separately and mechanically assembled to the frame.
- Seat and back are connected together using steel fabricated connector brackets.
- Stool frame shall be constructed from solid maple. Lumber to be dried to a final moisture content level between 6% - 8%.
- Legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 2 ½” x 1 1 ¼” tapering to 1 ¼” x 1 ¼” at bottom.
- Foot ring available in the following finishes:  
P38 Black (standard)  
P60 Satin Chrome  
P70 Satin Brass
- Includes nailed in nylon glides suitable for all floorings.