

1904-WSWB BRANDO BAR



OVERALL DIMENSIONS:

					
45.5	25	21	31.5	N/A	INCHES

DIMENSIONS ARE APPROXIMATE

YARDAGE:

COM: 2 yards per stool (based on based on plain, non-directional, no repeat textile)

SPECIFICATION:

- Back of shell constructed from 1/2" thick formed solid core plywood
- Seat constructed of 3/4" solid core plywood
- Foam applied on shell is high density CAL 117. Foam is 1 1/2" thick, 2.5 lbs. on the seat; 1" thick, 1.9 lbs. on the inside back and 1 1/2" thick, 1.5 lbs. on the outside back.
- Seat and back of the chair are upholstered separately and mechanically assembled to the frame.
- Seat and back are connected together using steel fabricated connector brackets.
- Stool frame shall be constructed from solid maple. Lumber to be dried to a final moisture content level between 6% - 8%.
- Legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 2 1/2" x 1 1/4" tapering to 1 1/4" x 1 1/4" at bottom.
- Foot ring available in the following finishes:
P38 Black (standard)
P60 Satin Chrome
P70 Satin Brass
- Includes nailed in nylon glides suitable for all floorings.