

1948 HAMLET STOOL SERIES



OVERALL DIMENSIONS:



DIMENSIONS ARE APPROXIMATE AND MAY VARY DEPENDING ON BASE STYLE

YARDAGE:

COM: 1.25 yards per chair (yardage based on plain, non-directional, no repeat material)

THIS PRODUCT REQUIRES MEMO SAMPLE OF FABRIC FOR TESTING AND APPROVAL

SPECIFICATION:

- Shell and seat on all models consist of a plywood core, wrapped in high density molded CAL TB117-2013 foam.
- Shell back, seat and sides are wrapped in Dacron and upholstered as specified. This item requires memo sample of fabric/COM for testing and approval prior to production.
- Tapered Wood legs (TWLG) are tapered and made from solid Ash wood. Leg is Ø38 mm at the top tapering down to Ø25 mm, available in any standard Isa wood finish. Includes a metal footrest, available in Polished Chrome, Satin Chrome or Black.
- Tapered Metal Legs (TMLG) are manufactured using 16 gauge steel tube. Leg is Ø38 mm at the top and tapers down to Ø16 mm. Available in any standard ISA powder coat or plated finishes (different price ranges).
- Slim Tapered Metal Legs (STLG) are manufactured using 16 gauge steel tube. Leg is Ø25 mm at the top and tapers down to Ø16 mm. Available in any standard ISA powder coat or plated finishes (different price ranges).
- Wood Swivel Base (WSB) are made from solid Ash wood. Leg is 2.5" x 1 3/8" at the top tapering down to 1.5" x 1 2/8" at bottom. Available in any standard Isa wood finish. Includes a metal footrest on the outside of the legs, available in Polished Chrome, Satin Chrome or Black.



- **Disc Base (DB)** Built of ½" thick, 18" diameter solid steel bottom plate; 3" diameter metal column and a 3/16" thick top plate. Includes a 16"dia. footrest built of ½" x ½" material. Available in any standard ISA powder coat or plated finish (different price range).
- Includes nail-in glides in nylon for the wood models (TWLG & WSB) and metal push-in glides for the metal legs (TMLG & STLG & DB).
- All stools are available in Counter Height (24" seat height) upon request.