

## 217 JAZZ LOUNGE CHAIR



## **SPECIFICATION:**

- Chair frame shall be constructed from solid kiln dried beech wood. Lumber to be dried to a final moisture content level between 6% 8%.
- Front legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 1 <sup>3</sup>/<sub>4</sub>" x 1 <sup>3</sup>/<sub>4</sub>" tapering to 1 <sup>1</sup>/<sub>4</sub>" x 1 <sup>1</sup>/<sub>4</sub>" at bottom.
- Rear legs to be constructed from single stock lumber cut to shape. Finished dimensions are 1" x 2" and tapers to the bottom.
- The seat rails are made from single stock lumber 2" x 3" and shaped to conform to the chair design and are glued dowelled and screwed together with corner blocks.
- The seat shall be built of <sup>3</sup>/<sub>4</sub>" thick solid core ply and applied to the solid hardwood frame. The seat is attached to the hardwood frame and screwed to the frame.
- The curved back is a single piece formed plywood screwed into the seat frame.
- Foam is 2" high density CAL 117 foam on the seat and ½" on the inside and outside back.
- All exposed wood is finished in any standard ISA wood finish. All legs receive nail-in nylon glides, suitable for most flooring types.