

### 309 CHARLIE STACK

---



**OVERALL DIMENSIONS:**



34.5      21      18      n/a      INCHES

**YARDAGE:**

*COM: 1.5 yards per chair (based on based on plain, non-directional, no repeat textile)*

### 1309 CHARLIE BAR

---



**OVERALL DIMENSIONS:**



44.5      19.5      17      29      INCHES

**YARDAGE:**

*COM: 1.5 yards per chair (based on based on plain, non-directional, no repeat textile)*

**SPECIFICATION:**

- Frame and all exposed wood shall be constructed from solid kiln dried beech wood. Lumber to be dried to a final moisture content level between 6% - 8%.
- Front legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 15/8" x 15/8" tapering to 1" x 1" at bottom.
- Rear legs to be constructed from single stock lumber cut to shape. Finished dimensions are 1 1/4" x 1 1/8" and tapers top and bottom. The top of the chair back is integrally joined to the back legs.



- The seat shall be ½” thick solid core beech wood ply and applied to the solid beech wood frame. The seat is attached to the beech wood frame and screwed to the frame.
- Back is curved by way of radio frequency constructed from solid beech plywood 7/8” x ¼” glued by way of mortise and tenon into the solid beech wood back frame and rail top and bottom. Bottom back rail is shaped from solid beech wood that is mortise and tenon glued into on the back legs.
- The chair frame and seat frame are connected together by dowels, corner blocks, bolts and glue.
- Foam is 2” high density on the seat.