

310 JERSEY STACK SIDE CHAIR



OVERALL DIMENSIONS:



YARDAGE:

COM: (1.5 yards each – based on plain, nondirectional, no repeat textile)

1310 JERSEY STOOL



OVERALL DIMENSIONS:

Н	\vdash	\blacksquare	Н	h	
44.5	19.5	17	29	n/a	INCHES

DIMENSIONS ARE APPROXIMATE

YARDAGE:

COM: (1.25 yards each – based on plain, nondirectional, no repeat textile)

SPECIFICATION:

- Chair/Barstool frame and all exposed wood shall be constructed from solid kiln dried beech wood. Lumber to be dried to a final moisture content level between 6% 8%.
- Front Legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 1 5/8" x 1 5/8" tapering to 1" x 1" at bottom
- Rear legs to be constructed from single stock lumber cut to shape. Finished dimensions are 1 ½" x 1 1/8" and tapers top and bottom. The top of the chair back is integrally joined to the back legs
- The seat shall be ½" thick solid core beech wood ply and applied to the solid beech wood frame. The seat is attached to the beech wood frame and screwed to the frame
- Back is curved by way of radio frequency constructed from solid beech wood 7/8" x ¼" glued by way of
 mortise and tenon into the solid beech wood back frame and rail top and bottom.

46 Dufflaw Road Toronto ON M6A 2W1 | 416-782-9100 | 1-800-881-3928 | www.havaseat.com | isa@havaseat.com



- A U-type stretcher 1" x 3/4" is attached by way of mortise and tenon into the front legs and screwed into the back legs.
- The stool also features the two front stretchers for added strength. The lower front stretcher includes a metal footrest, available in Black, Brass, Satin Aluminum finishes.
- The barstool and seat frame are connected together by dowels, corner blocks, bolts and glue. The frame/exposed wood is finished in any Standard ISA wood finish. A clear coat of urethane, low gloss is applied for added protection.
- Foam is 2" thick, high-density CAL-117 FR on the seat and 3/4" thick on the back.
- Stools are also available in Counter Height (24" seat height).
- Both the chair and stool include nail-in nylon glides on legs, suitable for most flooring types.