

341 ESPRESSO CHAIR



OVERALL DIMENSIONS:

| | | | | | |
|---|---|---|---|---|--------|
|  |  |  |  |  | |
| 33 | 19 | 18 | 18 | n/a | INCHES |

DIMENSIONS ARE APPROXIMATE

YARDAGE:

COM: 2 yards each (based on plain, non-directional, no repeat textile)

SPECIFICATION:

- Chair frame shall be constructed from solid kiln dried beech wood. Lumber to be dried to a final moisture content between 6% - 8%.
- Front Legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 15/8" x 15/8" tapering to 1 1/4" x 1 1/4" at bottom.
- Rear legs to be constructed from single stock lumber cut to shape. Finished dimensions are 1 1/4" x 1 1/4" and tapers top and bottom. The top of the chair back is integrally joined to the back legs.
- The seat shall be 5/8" thick plywood upholstered and applied to the solid beech wood frame. The seat is upholstered and attached to the beech wood frame and screwed to the frame
- Front, back and side stretchers are standard for reinforcement.
- Back is solid beech wood that is mortised and tenoned into the upper portion of the back legs and then upholstered.
- Side, front and back stretchers are mortised and tenoned into the legs for added strength.
- The chair frame and seat frame are connected together by dowels, corner blocks, bolts and glue.
- Upholstery is medium density CAL-117 FR foam box seat and pull-over back.
- All exposed natural woods are stained in any Standard ISA wood finish with polyurethane with a low-gloss finish.
- Floor contact points are nylon nail-in type glides.