

### 355 CAMBRIA SIDE CHAIR

---



**OVERALL DIMENSIONS:**



33.5    24.5    20.5    n/a    INCHES

**YARDAGE:**

*COM: 2 yards per chair (based on based on plain, non-directional, no repeat textile)*

### 356 CAMBRIA ARM CHAIR

---



**OVERALL DIMENSIONS:**



33.5    24.5    23.5    27    INCHES

**YARDAGE:**

*COM: 2 yards per chair (based on based on plain, non-directional, no repeat textile)*

**SPECIFICATION:**

- Chair shall be constructed from solid kiln dried maple. Lumber to be dried to a final moisture content between 6%-8%.
- Front legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 1½" x 1½" tapering to 1" x 1" at bottom.
- Rear legs to be constructed from single stock lumber cut to shape. Finished dimensions are 1½" x 1" and bottom 1" x 1".
- Front and rear legs and attached by a solid maple frame that is 1" x 3".



- Side stretchers run front to back leg and are dowelled and glued together.
- The chair frame and seat frame are connected together by dowels, corner blocks, bolts and glue.
- The seat shall be ½” thick solid core ply and applied to the solid maple frame. The seat is attached to the maple frame via screws. Foam and upholstery are applied after assembly.
- The arm design is connected to the back and integrally supported to the front leg for extra strength.