


1353 SALVADOR STOOL



OVERALL DIMENSIONS:



DIMENSIONS ARE APPROXIMATE

YARDAGE:

COM: (2 yards each – based on plain, non-directional, no repeat textile)

SPECIFICATION:

- Frame shall be constructed from solid kiln dried hardwood. Lumber to be dried to a final moisture content level between 6% - 8%.
- Front legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 1 ½" x 1 ½" tapering to 1 ¼" x 1 ¼" at bottom. Rear legs to be constructed from single stock lumber cut to shape. Finished dimensions are 1 ½" x 2" and tapers to 1 ¼" x 1 ½" at bottom.
- Side and front stretcher are added for stability. Front stretcher includes a metal footrest that can be finished in Black, Brass or Satin Aluminum.
- The seat rails are made from single stock lumber 2" x 3" and shaped to conform to the chair design and are glued dowelled and screwed together with corner blocks.
- The seat shall be ¾" thick solid core ply and applied to the solid hardwood frame. The seat is attached to the hardwood frame and screwed to the frame.
- The curved back is a single piece formed plywood screwed into the seat frame.
- Foam is 2" high density CAL TB117-2013 foam on the seat and ½" on the inside and outside back.
- Includes nail-in nylon glides, suitable for most flooring types.
- Also available in counter height (24" seat height).