

1830 BALTHAZAR STOOL SERIES



1830-TMLG



1830-STLG



1830-TWLG



1830-DB



1830-WSB

OVERALL DIMENSIONS:



40 21 22 29.5 n/a INCHES

DIMENSIONS ARE APPROXIMATE AND MAY VARY DEPENDING ON BASE STYLE

YARDAGE:

COM: 1.25 yards per chair (based on based on plain, non-directional, no repeat textile)

**Memo sample testing is required for this product, if fabric has not been previously approved*

SPECIFICATION:

- Stool starts with a cold molded foam shell, which is made from a metal frame injected with PU foam.
- Shell seat is then wrapped in ¼” high density CAL 117 FR foam.
- Shell back and sides is wrapped in Dacron.
- Available with the following bases:

Tapered Metal Leg (TMLG) - Manufactured using Ø38 mm, 16 gauge steel tube. Leg is Ø38 mm at the top and tapers down to Ø16 mm. Available in any standard ISA powder coat finish and P77 Polished Chrome.

Slim Tapered Metal Leg (STLG) - Manufactured using Ø16 mm steel tubing. Available in any standard ISA powder coat and plated finish.

Tapered Wood Leg (TWLG) – Made of solid Ash. Leg is Ø38 mm at the top tapering down to Ø25 mm. Available in any standard ISA wood finish.



Disc Base (DB) - Frame starts with a bottom ½” solid metal plate and covered with a round 16 gauge furniture grade cover. The column is 3” diameter 14 gauge metal with metal top mounting plate plates have adjustable glides in them to allow leveling on uneven floors.

Wood Swivel Base (WSB) - Frame to be constructed from solid maple. Lumber to be dried to a final moisture content level between 6% - 8%. Legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 2 ½” x 1 1 ¼” tapering to 1 ¼” x 1 ¼” at bottom. Available in any standard ISA wood finish.

- Stool version available in 24” seat height (counter), upon request.