

## 1889 BARRIO STOOL



1889-SMLG



1889-TMLG



1889-CNB



1889-TWLG

### OVERALL DIMENSIONS:



44.5    22    21    29.5    n/a    INCHES

### DIMENSIONS ARE APPROXIMATE AND MAY VARY DEPENDING ON BASE STYLE

### YARDAGE:

COM: 1 yard per 2 chairs (based on based on plain, non-directional, no repeat textile)

### SPECIFICATION:

- Back to be constructed from ½” thick formed solid core plywood.
- Seat to be ¾” thick solid core plywood
- Foam is to be CAL 117 2013 high density on the seat and back. Foam will be 1 ½” thick 2.5 lbs. on the seat, 1” thick 1.9 lbs. on the inside back, and ½” thick 1.5 lbs. on the outside back.
- Plywood legs are high frequency molded with 30 layers, 1 ⅛” thick. Top legs taper from 2” to 1 ¼” at the bottom. Profile is machined to an aesthetic V shape.
- Available with the following bases:

**Straight Metal Leg (SMLG)** - Manufactured using Ø16 mm steel tubing. Available in any standard ISA powder coat and plated finish.

**Tapered Metal Leg (TMLG)** - Manufactured using Ø38 mm, 16 gauge steel tube. Leg is Ø38 mm at the top and tapers down to Ø16 mm. Available in any standard ISA powder coat finish and P77 Polished Chrome.



**Cone Base (CNB)** - Manufactured using Ø38 mm, 16 gauge steel tube. Leg is Ø38 mm at the top and tapers down to Ø16 mm. Includes a 19" DIA foot ring. Available in any standard ISA powder coat finish and P77 Polished Chrome.

**Tapered Wood Leg (TWLG)** – Made of solid Ash. Leg is Ø38 mm at the top tapering down to Ø25 mm. Available in any standard ISA wood finish.

- Also available in counter height (24" seat height), upon request.
- Push-in glides will be used with available options in metal or polyethylene.