

443 / 444 / 1443 OSLO SERIES



443-WB OSLO

443-UBP OSLO

444-WB OSLO ARM

444-UBP OSLO ARM

1443-WB OSLO

1443-UBP OSLO

OVERALL 443-WB / 443-UBP SIDE CHAIR DIMENSIONS:



31.5 21 19 INCHES

OVERALL 444-WB / 444-UBP ARM CHAIR DIMENSIONS:



31.5 22.5 22 25.5 INCHES

OVERALL 1443-WB / 1443-UBP BARSTOOL DIMENSIONS:



42 19.5 18 30 INCHES

ALL DIMENSIONS ARE APPROXIMATE

COM YARDAGE:

443-UBP (Upholstered Back Pad): 0.75 yards for every 2 chairs (based on no repeat, non-directional material)

444-UBP (Upholstered Back Pad): 1 yard for every 2 chairs (based on no repeat, non-directional material)

1443-UBP (Upholstered Back Pad): 0.75 yards for every 2 stools (based on no repeat, non-directional material)

SPECIFICATION:

- Frames to be constructed of solid kiln dried beech-wood. Lumber to be dried to a final moisture content between 6% -8%.



- Front Legs to be constructed of single stock lumber. Finished dimension on Chair and Arm Chair at the top of leg to be approximately 1 ¼" x 1 ¼" tapering down to 1" x 1" at bottom. In barstool front legs at top to be 1 ½" x 1 ½" tapering down to 1" x 1" at bottom.
- Rear Legs to be constructed of single stock lumber. Finished dimension on Chair and Arm Chair at the top of leg to be approximately 1 ½" x 1 ¼" tapering down to 1" x 1" at bottom. In barstool front legs at top to be 1 ½" x 1 ½" tapering down to 1" x 1" at bottom.
- Seat consists of web construction and high density foam CAL-117 2013.
- The curved wooden back is attached to the rear leg frame via dowels and high performance glue.
- Front, back and stretchers are standard for added durability.
- Floor contact is smoothed with nylon nail-in glides.
- Side Chairs available Stack or Non-Stack.