






470 SAMMY SIDE CHAIR



OVERALL DIMENSIONS:

					
33.5	21.5	20	19	n/a	INCHES






YARDAGE:

COM: 1.5 yards per chair (based on based on plain, non-directional, no repeat textile)

1470 SAMMY BAR STOOL



OVERALL DIMENSIONS:

					
41.5	21.5	20	30	n/A	INCHES

YARDAGE:

COM: 1.25 yards per chair (based on based on plain, non-directional, no repeat textile)

SPECIFICATION:

- Chair frame shall be constructed from solid beech. Lumber to be dried to a final moisture content level between 6% - 8%.
- Front legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 1.5" tapering to 1 1/8" at bottom.
- Rear legs to be constructed from single stock lumber cut to shape. Finished dimensions at top of leg to be 1.5" tapering to 1 1/8" at bottom.
- The seat rails are made from single stock solid lumber and shaped to conform to the chair design and are glued dowelled and screwed together.
- The seat shall be 1/2" thick solid core ply applied to the solid hardwood frame. The seat is attached and screwed to the hardwood frame.
- The curved back is made of single piece formed plywood screwed onto the frame.
- 1/2" high density CAL 117 FR foam and Dacron wrap are applied to the seat. 1/2" thick foam is applied on the inside back and 1/4" thick foam is applied on the outside back.



- Bar and counter stools include a metal footrest on front stretcher. Foot rest is available in Black, Satin Aluminum or Brass finishes.
- Stools are also available in counter height (24" seat height).
- All items include nail-in nylon glides.