

## 870 / 871 / 1870 BOTTICELLI SERIES

---



870 Botticelli Side




871 Botticelli Arm



1870 Botticelli Stool

### OVERALL DIMENSIONS 870 SIDE CHAIR:



DIMENSIONS ARE APPROXIMATE

---

### OVERALL DIMENSIONS 871 ARM CHAIR:



DIMENSIONS ARE APPROXIMATE

---

### OVERALL DIMENSIONS 1870 STOOL:



DIMENSIONS ARE APPROXIMATE

---

### YARDAGE:

870 SIDE CHAIR: 1 yard each (based on based on plain, non-directional, no repeat textile)

871 ARM CHAIR: 1 yard each (based on based on plain, non-directional, no repeat textile)

1870 STOOL: 1 yard each (based on based on plain, non-directional, no repeat textile)



## SPECIFICATIONS:

- Chair and stool frame shall be constructed from solid kiln dried beech wood. Lumber to be dried to a final moisture content between 6% -8%.
- Front Legs to be constructed from single stock lumber. Finished dimension at the top of leg to be 1 5/8" x 1 5/8" tapering to 1" x 1" at bottom.
- Rear legs to be constructed from single stock lumber cut to shape. Finished dimensions are 1 1/4" x 1 1/8", tapering at the top and bottom. The top of the chair back is integrally joined to the back legs.
- The seat shall be 1/2" thick solid core beech wood ply and applied to the solid beech wood frame. The seat is attached to the beech wood frame and screwed to the frame
- U-bracing on legs is built in solid beech wood that is mortise and tenon glued and screwed onto the back legs.
- Stools feature a front stretchers for added support. The stretcher has a metal footrest that can be finished in black, brass or brushed aluminum.
- The chair frame and seat frame are connected together by dowels, corner blocks, bolts and glue.
- High density foam is 2" medium density on the seat. Foam meets CAL 117 FR. Upholstery is applied after assembly.
- Stools are available in bar height (30" seat height) and counter height (24" seat height).