

1473 OLA STOOL SERIES



1473-WS/WB
(Wood Seat and Back)



1473-USP/WB
(Uph. Seat Pad / Wood Back)

OVERALL DIMENSIONS:



41.5 19 18.5 30 INCHES

*DIMENSIONS MAY VARY SLIGHTLY.

COM YARDAGE:

1473-USP/WB (seat pad, wood back): 0.75 yard for every 02 chairs (based on no repeat, non-directional material)

SPECIFICATION:

- Stool frames are constructed of solid kiln dried beech wood. Lumber to be dried to a final moisture content level between 6% - 8%.
- The frame components are connected together by dowels, corner blocks, screws and glue.
- Legs are 1.5" diameter at the top, tapering down to 1" diameter at the bottom.
- The seat rail is 2.5" H. The wood seat panel is ¼" thick plywood and is attached to the main frame via screws and glue.
- The back rest consists of ½" thick bent plywood and is attached to the main frame via dowels and glue.
- The seat pad (USP version) is approximately ½" thick and consist of pliable wood board, covered in high-density foam, meeting CAL 117 FR. Upholstery is then applied, as specified.
- All exposed wood can be finished in any standard ISA wood finish. Frames then receive a clear urethane top coat in low gloss for added protection.
- All chairs include nail-in nylon glides suitable for most flooring types.
- Also Available in 24" seat height (counter height).